

CMSC 311, Fall 2009
Lab Assignment 2: Defusing a Binary Bomb
Assigned: Sept. 16
Due: Sept. 30

1 Introduction

The nefarious *Dr. Evil* has planted a slew of “binary bombs” on our machines. A binary bomb is a program that consists of a sequence of phases. Each phase expects you to type a particular string on *stdin*. If you type the correct string, then the phase is *defused* and the bomb proceeds to the next phase. Otherwise, the bomb *explodes* by printing "BOOM!!!" and then terminating. The bomb is defused when every phase has been defused.

There are too many bombs for us to deal with, so we are giving each group a bomb to defuse. Your mission, which you have no choice but to accept, is to defuse your bomb before the due date. Good luck, and welcome to the bomb squad!

Step 1: Get Your Bomb

Each group of students will attempt to defuse their own personalized bomb. Each bomb is a Linux binary executable file that has been compiled from a C program. To obtain your group’s bomb, one (and only one) of the group members should point your Web browser to the bomb request daemon at

`http://fireball.cs.umd.edu:15213`

Fill out the HTML form with your email address (this is not a team project), and then submit the form by clicking the “Submit” button. The request daemon will build your bomb and return it immediately to your browser in a `tar` file called `bombk.tar`, where k is the unique number of your bomb.

Save the `bombk.tar` file to a (protected) directory in which you plan to do your work. Then give the command: `tar xvf bombk.tar`. This will create a directory called `./bombk` with the following files:

- `README`: Identifies the bomb and its owners.
- `bomb`: The executable binary bomb.

- `bomb.c`: Source file with the bomb's main routine.

Also, if you make any kind of mistake requesting a bomb (such as neglecting to save it or typing the wrong group members), simply request another bomb.

Remember, each bomb is unique. If you request a new bomb, it will be different and you'll have to tell us which one you submitted.

Step 2: Defuse Your Bomb

Your job is to defuse the bomb.

You can use many tools to help you with this; please look at the **hints** section for some tips and ideas. The best way is to use your favorite debugger to step through the disassembled binary.

Each phase is worth 10 points, for a total of 60 points.

The phases get progressively harder to defuse, but the expertise you gain as you move from phase to phase should offset this difficulty. However, the last phase will challenge even the best students, so please don't wait until the last minute to start.

The bomb ignores blank input lines. If you run your bomb with a command line argument, for example,

```
linux> ./bomb psol.txt
```

then it will read the input lines from `psol.txt` until it reaches EOF (end of file), and then switch over to `stdin`. In a moment of weakness, Dr. Evil added this feature so you don't have to keep retyping the solutions to phases you have already defused.

To avoid accidentally detonating the bomb, you will need to learn how to single-step through the assembly code and how to set breakpoints. You will also need to learn how to inspect both the registers and the memory states. One of the nice side-effects of doing the lab is that you will get very good at using a debugger. This is a crucial skill that will pay big dividends the rest of your career.

Logistics

Any clarifications and revisions to the assignment will be posted on the class forum.

You should do the assignment on the UMD OIT GRACE cluster Linux machines. The valid machines are `scary.umd.edu` or `baby.umd.edu`. In fact, there is a rumor that Dr. Evil really is evil, and the bomb will always blow up if run elsewhere. There are several other tamper-proofing devices built into the bomb as well, or so they say.

Hand-In

You will hand in a text file named "psol.txt" containing all of the passwords used to defuse your bomb such that it can be tested from the command line as in:

```
linux> ./bomb psol.txt
```

When you run the bomb, it will send a result message to the server. The scores for each bomb are automatically posted by the server here:

```
http://www.cs.umd.edu/~jims/lab2fall09.html
```

Hints (*Please read this!*)

There are many ways of defusing your bomb. You can examine it in great detail without ever running the program, and figure out exactly what it does. This is a useful technique, but it not always easy to do. You can also run it under a debugger, watch what it does step by step, and use this information to defuse it. This is probably the fastest way of defusing it.

We do make one request, *please do not use brute force!* You could write a program that will try every possible key to find the right one. But this is no good because we haven't told you how long the strings are, nor have we told you what characters are in them. Even if you made the (wrong) assumptions that they all are less than 80 characters long and only contain letters, then you will have 26^{80} guesses for each phase. This will take a very long time to run, and you will not get the answer before the assignment is due.

There are many tools which are designed to help you figure out both how programs work, and what is wrong when they don't work. Here is a list of some of the tools you may find useful in analyzing your bomb, and hints on how to use them.

- gdb

The GNU debugger, this is a command line debugger tool available on virtually every platform. You can trace through a program line by line, examine memory and registers, look at both the source code and assembly code (we are not giving you the source code for most of your bomb), set breakpoints, set memory watch points, and write scripts. Here are some tips for using gdb.

- To keep the bomb from blowing up every time you type in a wrong input, you'll want to learn how to set breakpoints.
- The CS:APP Student Site at <http://csapp.cs.cmu.edu/public/students.html> has a very handy single-page gdb summary.
- For other documentation, type "help" at the gdb command prompt, or type "man gdb", or "info gdb" at a Unix prompt. Some people also like to run gdb under gdb-mode in emacs.

- objdump -t

This will print out the bomb's symbol table. The symbol table includes the names of all functions and global variables in the bomb, the names of all the functions the bomb calls, and their addresses. You may learn something by looking at the function names!

- `objdump -d`

Use this to disassemble all of the code in the bomb. You can also just look at individual functions. Reading the assembler code can tell you how the bomb works.

Although `objdump -d` gives you a lot of information, it doesn't tell you the whole story. Calls to system-level functions are displayed in a cryptic form. For example, a call to `sscanf` might appear as:

```
8048c36: e8 99 fc ff ff call 80488d4 <_init+0x1a0>
```

To determine that the call was to `sscanf`, you would need to disassemble within `gdb`.

- `strings`

This utility will display the printable strings in your bomb.

Looking for a particular tool? How about documentation? Don't forget, the commands `apropos` and `man` are your friends. In particular, `man ascii` might come in useful. Also, the web may also be a treasure trove of information. If you get stumped, feel free to ask your TA for help.