

InterComm Toolkit

Norman Lo and Alan Sussman

University of Maryland

Motivation

- Simulation of complex systems requires multiple physical models
- Need the capability to move data between coupled models (MxN transfer)
- CCA components allow the reusability of common computational tasks
- With CCA-InterComm toolkit, along with the growing collection of CCA toolkits, complex systems can be developed in a simpler way.

Creating the InterComm Toolkit

- Bocca provides a simplified way to create and maintain the CCA components
- All the necessary SIDLs, skeleton files, makefiles, and etc are automatically generated.
- Only need to fill in the *.impl* files.
- InterComm and PVM libraries are linked by modifying *make.vars.user*.
- A pointer lookup table is used to pass pointers between components.

Components

Schedule

- Prepares InterComm for schedule building
- Provides XJDPort and uses RegionPort

ICRegion

- Calculates the InferComm region information
- Provides RegionPort

Communicate

- Send or Receive data
- Provides CommPort

CDriver/CDriverOther

- Drives the InterComm components
- Uses XJDPort and CommPort

Driver Components

CDriver

0	1	2
3	4	5
6	7	8


CDriverOther

-1	-1	-1	-1	-1
-1	0	1	2	-1
-1	3	4	5	-1
-1	6	7	8	-1
-1	-1	-1	-1	-1



15	-1	-1	-1
-1	-1	-1	-1
-1	-1	-1	-1
-1	-1	-1	0

0	1	2	3
4	5	6	7
8	9	10	11
12	13	14	15



Ports

- **XJDPort – returns the XJD_index contains InterComm information**

```
int computeSchedule(in int progame_index, in int xjd_read,  
                  in int rank,           // Initialize info  
                  in int ndims, in int arrayOrder, in int count,  
                  in int tasks_index, in int indices_index,  
                  in int type,         // Descriptor info  
                  in int rgname_index, in int rgnset_index,  
                  in int rgnsize, in int data_index); // Region info
```


- **RegionPort – returns 0 if success, -1 otherwise**

```
int computeRegion(in int ndims, in int rgnset_index, in int xjd_index,  
                 in int rgnsize, in int rgname_index,  
                 in int desc_index, in int data_index);
```

- **CommPort – returns 0 if success, -1 otherwise**

```
int communicate(in int xjd_index, in int rgname_index, in int  
              direction, in int final_flag);
```

Connection in GUI



Flowchart

