### Announcements

- Reading
  - Today: Chapter 5 (5.5-5.6)
- Project #3
  - Is on the web
- Midterm #1
  - Next Tuesday Oct. 9
  - Cover material through today's lecture

# Load Shedding

- When all else fails, routers drop (discard) packets
- Policy question: what packets to drop?
  - oldest ones: they are likely to be useless now
  - newest ones: helps to close open window in file transfer
  - less important ones
    - requires cooperation of application
    - in MPEG I frames are more important than B frames
  - drop all related packets
    - fragmentation: loss of one packet renders others useless
    - requires information from higher levels
- Preemptive shedding
  - when traffic starts to get high, dropping packets can prevent additional congestion

## **RSVP - Multicast Bandwidth Reservation**

- Receivers send request to reserve BW up spanning tree
- Routers propagate request up tree
  - only sent if greater than prev. request for this group
- Dest. can request BW for multiple alternative sources
  - routers only allocate bandwidth for maximum channel request





# Firewalls

#### • A way to limit information flow

- selective forwarding of information based on **policy**
- policy: rules about what should be permitted
- mechanism: way to enforce policy

#### • Can be implemented at many levels

- at higher layers have more information
- at lower layers can share filtering between multiple higher level entities

#### Possible Layers

- link layer: filter based on MAC address
- network layer: filter based on source/destination, transport
- transport: filter based on service (e.g. port number)
- application: filter based on user name in email, based on content

# Tunneling

#### • Problem

- Source and Destination are compatible
- something in the middle is not compatible
- Solution: Tunnel though the middle
  - only multi-protocol routers need to understand conversion
  - possible to tunnel through almost anything
    - can tunnel IP through IP (for mobile computing perhaps)



6

## **Internet Routing**

- Use two levels of routing
- local (subnet) level routing
- Internet routing between multi-protocol gateways
  - multiple protocol gateways are generally fully connected
    - since they hide the underlying network
  - policies (politics) can dictate acceptable routes
    - don't route IBM packets on the Microsoft network
    - all packets starting and ending in Canada must stay in Canada
- Can use any of the standard routing algorithms
  - link-state
  - distance vector

# Interior Gateway Routing Protocol

- Routes within a single Autonomous System (AS)
  - An AS contains
    - areas (collection of one or more subnets)
    - backbone (to interconnect areas within AS)
  - Also Called Open Shortest Path First (OSPF)
- Divides routers into four classes
  - Internal only within the area
  - Area boarder routers connect two or more areas
  - Backbone routers connect to backbone
  - AS boundary routers talk to other AS
- Exchanges info between adjacent routers
  - not the same as a neighbor since could have many hops in-between
- Uses link-state
  - flooding with sequence numbers
  - supports multiple metrics: throughput, reliability, delay
  - backbone computes inter-area routes

