15-213 "The Class That Gives CMU Its Zip!"

Introduction to Computer Systems

Randal E. Bryant August 27, 2002

Topics:

- **Theme**
- **■** Five great realities of computer systems
- How this fits within CS curriculum

Course Theme

Abstraction is good, but don't forget reality!

Courses to date emphasize abstraction

- Abstract data types
- Asymptotic analysis

These abstractions have limits

- Especially in the presence of bugs
- Need to understand underlying implementations

Useful outcomes

- Become more effective programmers
 - Able to find and eliminate bugs efficiently
 - Able to tune program performance
- Prepare for later "systems" classes in CS & ECE
 - Compilers, Operating Systems, Networks, Computer Architecture, Embedded Systems

Int's are not Integers, Float's are not Reals

Examples

- Is $x^2 \ge 0$?
 - Float's: Yes!
 - Int's:
 - » 40000 * 40000 --> 1600000000
 - » 50000 * 50000 --> ??
- Is (x + y) + z = x + (y + z)?
 - Unsigned & Signed Int's: Yes!
 - Float's:
 - » (1e20 + -1e20) + 3.14 --> 3.14
 - » 1e20 + (-1e20 + 3.14) --> ??

Computer Arithmetic

Does not generate random values

Arithmetic operations have important mathematical properties

Cannot assume "usual" properties

- Due to finiteness of representations
- Integer operations satisfy "ring" properties
 - Commutativity, associativity, distributivity
- Floating point operations satisfy "ordering" properties
 - Monotonicity, values of signs

Observation

- Need to understand which abstractions apply in which contexts
- Important issues for compiler writers and serious application programmers

You've got to know assembly

Chances are, you'll never write program in assembly

Compilers are much better & more patient than you are

Understanding assembly key to machine-level execution model

- Behavior of programs in presence of bugs
 - High-level language model breaks down
- **Tuning program performance**
 - Understanding sources of program inefficiency
- Implementing system software
 - Compiler has machine code as target
 - Operating systems must manage process state

- 5 - 15-213, F'02

Assembly Code Example

Time Stamp Counter

- Special 64-bit register in Intel-compatible machines
- Incremented every clock cycle
- Read with rdtsc instruction

Application

- Measure time required by procedure
 - In units of clock cycles

```
double t;
start_counter();
P();
t = get_counter();
printf("P required %f clock cycles\n", t);
```

-6- 15-213, F'02

Code to Read Counter

-7-

- Write small amount of assembly code using GCC's asm facility
- Inserts assembly code into machine code generated by compiler

```
static unsigned cyc_hi = 0;
static unsigned cyc_lo = 0;

/* Set *hi and *lo to the high and low order bits
  of the cycle counter.

*/
void access_counter(unsigned *hi, unsigned *lo)
{
    asm("rdtsc; movl %%edx,%0; movl %%eax,%1"
        : "=r" (*hi), "=r" (*lo)
        :
        : "%edx", "%eax");
}
```

15-213, F'02

Code to Read Counter

```
/* Record the current value of the cycle counter. */
void start counter()
    access counter(&cyc hi, &cyc lo);
/* Number of cycles since the last call to start counter. */
double get counter()
   unsigned ncyc hi, ncyc lo;
    unsigned hi, lo, borrow;
    /* Get cycle counter */
    access counter(&ncyc hi, &ncyc lo);
    /* Do double precision subtraction */
    lo = ncyc lo - cyc lo;
   borrow = lo > ncyc lo;
    hi = ncyc hi - cyc hi - borrow;
    return (double) hi * (1 << 30) * 4 + lo;
```

– 8 – 15-213, F'02

Measuring Time

Trickier than it Might Look

Many sources of variation

Example

Sum integers from 1 to n

n	Cycles	Cycles/n
100	961	9.61
1,000	8,407	8.41
1,000	8,426	8.43
10,000	82,861	8.29
10,000	82,876	8.29
1,000,000	8,419,907	8.42
1,000,000	8,425,181	8.43
1,000,000,000	8,371,2305,591	8.37

- 9 - 15-213, F'02

Memory Matters

Memory is not unbounded

- It must be allocated and managed
- Many applications are memory dominated

Memory referencing bugs especially pernicious

■ Effects are distant in both time and space

Memory performance is not uniform

- Cache and virtual memory effects can greatly affect program performance
- Adapting program to characteristics of memory system can lead to major speed improvements

- 10 - 15-213, F'02

Memory Referencing Bug Example

```
main ()
{
  long int a[2];
  double d = 3.14;
  a[2] = 1073741824; /* Out of bounds reference */
  printf("d = %.15g\n", d);
  exit(0);
}
```

	Alpha	MIPS	Linux
-g	5.30498947741318e-315	3.1399998664856	3.14
-0	3.14	3.14	3.14

(Linux version gives correct result, but implementing as separate function gives segmentation fault.)

15-213, F'02

Memory Referencing Errors

C and C++ do not provide any memory protection

- Out of bounds array references
- Invalid pointer values
- Abuses of malloc/free

Can lead to nasty bugs

- Whether or not bug has any effect depends on system and compiler
- Action at a distance
 - Corrupted object logically unrelated to one being accessed
 - Effect of bug may be first observed long after it is generated

How can I deal with this?

- Program in Java, Lisp, or ML
- Understand what possible interactions may occur
- Use or develop tools to detect referencing errors

Memory Performance Example

Implementations of Matrix Multiplication


Multiple ways to nest loops

```
/* ijk */
for (i=0; i<n; i++) {
  for (j=0; j<n; j++) {
    sum = 0.0;
    for (k=0; k<n; k++)
      sum += a[i][k] * b[k][j];
    c[i][j] = sum;
}
}</pre>
```

```
/* jik */
for (j=0; j<n; j++) {
  for (i=0; i<n; i++) {
    sum = 0.0;
    for (k=0; k<n; k++)
      sum += a[i][k] * b[k][j];
    c[i][j] = sum
  }
}</pre>
```


- 13 - 15-213, F'02

Matmult Performance (Alpha 21164)



- 14 - 15-213, F'02

Blocked matmult perf (Alpha 21164)



- 15 - 15-213, F'02

There's more to performance than asymptotic complexity

Constant factors matter too!

- Easily see 10:1 performance range depending on how code written
- Must optimize at multiple levels: algorithm, data representations, procedures, and loops

Must understand system to optimize performance

- How programs compiled and executed
- How to measure program performance and identify bottlenecks
- How to improve performance without destroying code modularity and generality

- 16 - 15-213, F'02

Computers do more than execute programs

They need to get data in and out


■ I/O system critical to program reliability and performance

They communicate with each other over networks

- Many system-level issues arise in presence of network
 - Concurrent operations by autonomous processes
 - Coping with unreliable media
 - Cross platform compatibility
 - Complex performance issues

- 17 - 15-213, F'02

Role within Curriculum



15-213, F'02 -18-

Course Perspective

Most Systems Courses are Builder-Centric

- **Computer Architecture**
 - Design pipelined processor in Verilog
- Operating Systems
 - Implement large portions of operating system
- Compilers
 - Write compiler for simple language
- Networking
 - Implement and simulate network protocols

- 19 - 15-213, F'02

Course Perspective (Cont.)

Our Course is Programmer-Centric

- Purpose is to show how by knowing more about the underlying system, one can be more effective as a programmer
- Enable you to
 - Write programs that are more reliable and efficient
 - Incorporate features that require hooks into OS
 - » E.g., concurrency, signal handlers
- Not just a course for dedicated hackers
 - We bring out the hidden hacker in everyone
- Cover material in this course that you won't see elsewhere

– 20 – 15-213, F'02