

AMSC/CMSC 661 Scientific Computing II  
Spring 2005  
Solution of Elliptic PDEs  
Part 1  
Dianne P. O'Leary  
©2005

These notes are based on the 2003 textbook  
of Stig Larsson and Vidar Thomée.

---

Elliptic Partial Differential Equations

---

The plan:

- The problem and boundary conditions
- **An important special case**
- A motivating problem
- The Maximum Principle
- The Green's function
- The variational formulation
- Solution and error estimates using finite differences
- Solution and error estimates using finite elements

Note the parallel with ODE-BVP presentation.

---

The philosophy:

- Emphasize what is different.
- Omit proofs if we have seen the main idea before.
- Concentrate on computational aspects.

**Reference:** Chapters 3-5.

---

The problem and boundary conditions (p. 25)

Find the function  $u(x)$  that satisfies

$$Au = -\nabla \cdot (a \nabla u) + b \nabla u + cu = f \text{ in } \Omega \subset \mathcal{R}^d$$

where the functions  $a(x), b(x), c(x), f(x)$  are given, subject to appropriate boundary conditions on  $\Gamma = \bar{\Omega} - \Omega$ :

- The **Dirichlet problem** specifies function values.  $u(x) = g(x)$  for  $x \in \Gamma$ .
- The **Neumann problem** specifies the normal derivative.

$$\frac{\partial u(x)}{\partial n} = g(x)$$

- **Robin's boundary conditions** specify some linear combination.

$$a \frac{\partial u(x)}{\partial n} + h(u - g) = 0$$

for  $x \in \Gamma$ .

- **Mixed boundary conditions** specify Dirichlet conditions on part of  $\Gamma$  and Neumann conditions on the rest.

### Assumptions:

- The coefficients  $a$ ,  $b$ , and  $c$  may depend on  $x$ .
- The coefficients  $a$ ,  $b$ , and  $c$  are **smooth** functions and so are  $f$  and  $g$ ; i.e., they have as many continuous derivatives as we need.
- $a(x) \geq a_0 > 0$  for  $x \in \bar{\Omega}$ . (Why?)
- $c(x) \geq 0$  for  $x \in \bar{\Omega}$ . (The reason is not as obvious.)

### An important special case: origin of harmonic functions

$$\mathcal{A}u = -\nabla \cdot (a \nabla u) + b \nabla u + cu = f \text{ in } \Omega$$

**Poisson's equation** (p. 26) results from setting  $a = 1$ ,  $b = 0$ ,  $c = 0$ . For  $(x, y, z) \in \mathcal{R}^3$ , this gives

$$-\Delta u \equiv -u_{xx} - u_{yy} - u_{zz} = f(x, y, z)$$

and if  $f = 0$ , we call this **Laplace's equation** and the solutions are **harmonic functions**.

This problem is well-studied, and analytic solution formulas exist for many domains  $\Omega$ . In Section 3.3, the formula is derived for  $\mathcal{R}^2$  when  $\Gamma$  is a circle, but we will skip this.

### Principle of superposition

Suppose we have solved two somewhat simpler problems:

$$\begin{aligned} \mathcal{A}v &= 0 \text{ in } \Omega, & v &= g \text{ on } \Gamma \\ \mathcal{A}w &= f \text{ in } \Omega, & w &= 0 \text{ on } \Gamma \end{aligned}$$

Then  $u = v + w$  solves our original problem.

This trick can be used to simplify analysis and computation.

---

### A motivating problem (Selvadurai, p. 236)

Here is an example of how ODE-BVPs arise in modeling **physical problems**.

- Suppose we have a piece of steel that is
  - **homogeneous** (of uniform content).
  - **isotropic** (with properties independent of direction of measurement).
- We know that steel **conducts heat**: it feels cold to the touch, because it conducts heat away from our finger.
- **Fourier** (1768-1830) derived a good model of this heat conduction: **Over a small length of time  $\Delta t$ , the amount of heat  $\Delta Q$  entering or escaping from a small piece of the metal bounded by a surface with area  $\Delta A$  is proportional to the rate at which the the temperature  $T$  changes normal to the surface.** (i.e., proportional to the 2nd derivative.)

We no longer need the wild assumptions we used for the ODE:

- The steel is infinite in  $y$  and  $z$  (or at least so large that it doesn't matter), but stretches between  $x = 0$  and  $x = 1$ ,
- and any external source of heat is applied at  $(0, y, z)$  for all values of  $y$  and  $z$ , so the only direction left to study is  $x$ .

Let's see what happens.

According to Fourier's model, the amount of heat entering a volume  $V$  of steel is

$$\int_V \nabla \cdot (a \nabla T) dV$$

where  $a$  is the proportionality between temperature and heat. (This is known as the **thermal conductivity** of the steel.)

If there is a heat source  $f$  within that volume, then it generates an amount of heat equal to

$$\int_V f dV.$$

The heat contained in  $V$  is

$$\int_V \rho c \frac{\partial T}{\partial t} dV$$

where  $\rho$  and  $c$  are two constants depending on the material:  $\rho$  is the **mass-density** of the steel and  $c$  is its **specific heat**.

To balance things out, we must have

$$\int_V \left( \nabla \cdot (a \nabla T) + f - \rho c \frac{\partial T}{\partial t} \right) dV = 0,$$

and taking limits over small volumes yields

$$\nabla \cdot (a \nabla T) + f = \rho c \frac{\partial T}{\partial t}.$$

Finally, if we assume **steady state**, in which  $T$  is unchanging, we obtain the equation

$$\nabla \cdot (a \nabla T) + f = 0,$$

and we can solve this for values of  $T$  in the interior of the steel once we know what is happening at the boundary.

**With such physical problems in mind, we return to the study of the theory of elliptic PDEs.**

### The Maximum Principle (p. 26)

$$\mathcal{A}u = -\nabla \cdot (a \nabla u) + b \nabla u + cu = f \text{ in } \Omega$$

**Theorem 3.1a (p. 26):** Assume

- $u \in \mathcal{C}^2(\bar{\Omega})$ ;
- $\mathcal{A}u \leq 0$  in  $\Omega$ .

Then

- If  $c = 0$ , then

$$\max_{x \in \bar{\Omega}} u(x) = \max_{x \in \Gamma} u(x)$$

- If  $c(x) \geq 0$  for  $x \in \Omega$ , then

$$\max_{x \in \Omega} u(x) \leq \max(\max_{x \in \Gamma} u(x), 0).$$

Compare: p.16

### The Minimum Principle

$$\mathcal{A}u = -\nabla \cdot (a \nabla u) + b \nabla u + cu = f \text{ in } \Omega$$

**Theorem 3.1b (p. 26):** Assume

- $u \in \mathcal{C}^2(\bar{\Omega})$ ;
- $\mathcal{A}u \geq 0$  in  $\Omega$ .

Then

- If  $c = 0$ , then

$$\min_{x \in \Omega} u(x) = \min_{x \in \Gamma} u(x)$$

- If  $c(x) \geq 0$  for  $x \in \Omega$ , then

$$\min_{x \in \Omega} u(x) \geq \min(\min_{x \in \Gamma} u(x), 0).$$

Compare: p.16

### Uses of the Maximum Principle

- Bounding the solution in terms of the data.
- Proving uniqueness of solutions.
- Proving stability of solutions.
- Monotonicity properties.

### Bounding the solution in terms of the data

**Theorem 3.2 (p. 27):** If  $u \in \mathcal{C}^2$ , then

$$\|u\|_{\mathcal{C}(\bar{\Omega})} \leq \|u\|_{\mathcal{C}(\Gamma)} + C\|\mathcal{A}u\|_{\mathcal{C}(\bar{\Omega})}$$

where the constant  $C$  depends on  $a, b$ , and  $c$ .

**Compare:** p.17

**Usefulness:** Even if  $f(x)$  is not always  $\geq 0$  in  $\Omega$ , we have an upper and lower bound on the solution.

---

### Proving uniqueness

**Corollary 3.2a:** Our problem has a unique solution.

**Proof:** (as before) Suppose we have two solutions  $u$  and  $v$ , and let  $w = u - v$ . Then

$$\begin{aligned} \mathcal{A}w &= 0 && \text{in } \Omega, \\ w &= 0 && \text{on } \Gamma \end{aligned}$$

Therefore, Theorem 3.2 tells us that  $w(x) = 0$  for  $x \in \Omega$ , so  $u = v$ .  $\square$

---

### Proving stability

**Corollary 3.2b:** Our problem is **stable**: small changes in the data make small changes in the solution.

**Compare:** p.17

**Proof:** (as before) Suppose that

$$\begin{aligned} \mathcal{A}u &= f_1 \text{ in } \Omega, \quad u = g_1 \text{ on } \Gamma, \\ \mathcal{A}v &= f_2 \text{ in } \Omega, \quad v = g_2 \text{ on } \Gamma. \end{aligned}$$

Then, letting  $w = u - v$ , we see that

$$\begin{aligned} \mathcal{A}w &= f_1 - f_2 && \text{in } \Omega, \\ w &= g_1 - g_2 && \text{on } \Gamma. \end{aligned}$$

Now apply the stability estimate Theorem 3.2 to  $w$ :

$$\|w\|_{\mathcal{C}(\bar{\Omega})} \leq \|g_1 - g_2\|_{\mathcal{C}(\Gamma)} + C\|f_1 - f_2\|_{\mathcal{C}(\bar{\Omega})},$$

and stability is established.  $\square$

---

### The Green's function (p. 30)

$$\mathcal{A}u = -\nabla \cdot (a \nabla u) + b \nabla u + cu = f \text{ in } \Omega$$

For convenience, again we work with a special case:  $b = 0$ .

Recall from ODE-BVP that the **Green's function** gives us a formula for the solution to our problem in terms of simpler problems:

- First handle the function  $f$ .
- Then consider the boundary conditions.

The derivation for PDEs is a bit more complicated, and uses the **weak formulation** of the problem

$$(\mathcal{A}u, \phi) = (f, \phi)$$

for all  $\phi \in C_0^\infty(\mathcal{R}^d)$ .

**Note:** We define the **adjoint operator**  $\mathcal{A}^*$  as the operator that satisfies

$$(\mathcal{A}u, \phi) = (u, \mathcal{A}^*\phi)$$

for all  $u, \phi$ . Since  $b = 0$ , it can be shown that  $\mathcal{A}^* = \mathcal{A}$ : i.e.,  **$\mathcal{A}$  is self-adjoint**.

**Our goals:** To prove that a solution exists, and to express the solution in terms of the solution to simpler problems.

We express our solution in terms of the **fundamental solution**  $U$  that satisfies

$$\mathcal{A}U = \delta$$

where  $\delta$  is the **Dirac delta-function** (p. 241), defined to be 0 when  $x \neq 0$  and to have an integral of 1. **(A mathematician would not like this definition, but it will do.)**

Note that this means that

$$(U, \mathcal{A}\phi) = \phi(0).$$

We call  $U$  the **Green's function**.

**Theorem 3.4 (Green's Function Theorem) (p. 30)** If  $f \in C_0^1(\mathcal{R}^d)$ , then the solution to the problem  $\mathcal{A}u(x) = f(x)$  for  $x \in \mathcal{R}^d$  is

$$u(x) = \int_{\mathcal{R}^d} U(x-y)f(y)dy.$$

**Notes:**

- For some problems (e.g., Poisson's equation, p. 31), the function  $U$  is known explicitly, so the solution to the differential equation **on the infinite domain** with  $f$  arbitrary can be computed by integration. Easy!
- For finite domains, we need to impose boundary conditions. This leads to a numerical technique called the **boundary integral method** (older terminology: capacitance matrix techniques), but we won't study it in this course. See Section 14.4 if you are interested.

**Proof:** (Rather different from the ODE-BVP techniques).

Let  $z = x - y$ . Then

$$\int_{\mathcal{R}^d} U(x - y) \mathcal{A}\phi(x) dx = \int_{\mathcal{R}^d} U(z) \mathcal{A}\phi(z + y) dz = \phi(y).$$

Therefore,

$$\begin{aligned} (u, \mathcal{A}\phi) &= \int_{\mathcal{R}^d} \int_{\mathcal{R}^d} U(x - y) f(y) dy \mathcal{A}\phi(x) dx \\ &= \int_{\mathcal{R}^d} \int_{\mathcal{R}^d} U(x - y) \mathcal{A}\phi(x) dx f(y) dy && \text{interchanging order of integration} \\ &= \int_{\mathcal{R}^d} \phi(y) f(y) dy && \text{from our previous equation} \\ &= (f, \phi). \end{aligned}$$

We have assumed enough smoothness to use integration by parts, so we get

$$(u, \mathcal{A}\phi) = (\mathcal{A}u, \phi) = (f, \phi)$$

for all  $\phi \in C_0^\infty(\mathcal{R}^d)$ , so we have a solution to the problem  $\mathcal{A}u = f$ , as desired.  $\square$

### The variational formulation (p. 32)

We have already hinted at the variational formulation, a powerful tool for solving our pde.

### A weak formulation of our problem

$$\begin{aligned} \mathcal{A}u &= -\nabla \cdot (a \nabla u) + b \nabla u + cu = f \text{ in } \Omega \\ u &= \mathbf{0} \text{ on } \Gamma. \end{aligned}$$

### A change in assumptions:

- $a, b, c$  are smooth functions,



- $a(x) \geq a_0 > 0 \quad x \in \Omega$ ,
- $c(x) - \nabla b(x)/2 \geq 0$  for  $x \in \Omega$ .

Now choose an **arbitrary** function  $v \in C_0^1$ , and notice that

$$(\mathcal{A}u, v) = \int_{\Omega} (-\nabla \cdot (a \nabla u) + b \nabla u + cu) \mathbf{v} dx = \int_{\Omega} f \mathbf{v} dx = (f, v).$$

Now use integration by parts on the first term:

$$(\mathcal{A}u, v) = \int_{\Omega} (a \nabla u \cdot \nabla \mathbf{v} + b \nabla u v + cuv) dx = \int_{\Omega} f \mathbf{v} dx.$$

### Technicalities:

- $C_0^1$  is dense in  $H_0^1$ , so we can take  $v \in H_0^1$ .
- The solution  $u$  lives in  $H_0^1$ , so this is good.

So we have shown that if  $u$  solves our PDE, then  $u$  satisfies the **weak formulation**:

Find  $u \in H_0^1(\Omega)$  such that

$$a(u, v) \equiv (\mathcal{A}u, v) = \int_{\Omega} (a \nabla u \cdot \nabla \mathbf{v} + b \nabla u v + cuv) dx = \int_{\Omega} f \mathbf{v} dx \equiv (f, v)$$

for all  $v \in H_0^1(\Omega)$ .

The converse is not quite true; we say that  $u$  is a weak solution of our problem if  $u \in H_0^1$  satisfies the variational form of the problem, but it must be in  $C^2$  (in fact,  $H^2 \cap H_1^0$ ) to solve the **strong** (original) form of the problem.

### In weakness there is strength

The weak formulation has two important uses:

- It provides a set of numerical methods, called **Galerkin methods**. These come from enforcing  $a(u, v) = (\mathbf{f}, \mathbf{v})$  over a **subspace** of  $H_0^1$ . We'll follow up on this when we discuss **finite element methods**.
- It provides an alternative **existence proof** for the solution.

### Existence and uniqueness for the solution to the weak problem

**Theorem 3.6 (p. 33):** Under our assumptions  $a(x) \geq a_0 > 0$  and  $c(x) - \nabla b(x)/2 \geq 0$  for  $x \in \Omega$ , if  $f \in L_2$ , then there exists a unique solution of  $a(u, v) = (f, v)$  for all  $v \in H_0^2$ , with  $\|u\|_1 \leq C\|f\|$ , and this solution solves  $\mathcal{A}u = f$  in  $\Omega$  with  $u = 0$  on  $\Gamma$ .

Compare with p. 22.

---

### Another important tool: minimization of energy

If  $b = 0$ , then  $a(u, v) = a(v, u)$ , so  $a$  is both **self-adjoint** (symmetric) and **positive definite**. In this case, we can find the solution by minimizing

$$F(u) \equiv \frac{1}{2}a(u, u) - (f, u)$$

for  $u \in H_0^1$ .

This principle, **Dirichlet's principle** (Theorem 3.7) is an important computational tool.

**Physical interpretation:** Suppose we are modeling an elastic membrane attached at its boundary. Then

- $F(u)$  is the **potential energy** of the membrane, where  $u$  is the deflection.
- $a(u, u)$  is the **internal elastic energy**.
- $(f, u)$  is the **load potential**
- In physics, this is sometimes called the principle of **minimizing potential energy** or **minimizing virtual work**.

---

### Other boundary conditions

We derived the weak formulation for the **homogeneous Dirichlet boundary condition**. What about other cases?

**Nonhomogeneous Dirichlet:**  $u = g$  on  $\Gamma$ .

Find  $u \in H^1$  such that

$$a(u, v) = (\mathbf{f}, \mathbf{v})$$

for all  $v \in H_0^1$ , with  $\gamma u = g$ .

**Homogeneous Neumann:**  $\partial u / \partial n = 0$  on  $\Gamma$ . (Assume  $c(x) \geq c_0 > 0$  on  $\Omega$ .)

Find  $u \in H^1$  such that

$$a(u, v) = (\mathbf{f}, \mathbf{v})$$

for all  $v \in H^1$ .

(The boundary condition comes into the integration-by-parts formula; it is not enforced explicitly but instead follows **naturally** from the formulation.)

**Existence, uniqueness**, and stability can be established (pp. 34-37).

---

### Regularity (p. 37)

**Theorem 2.6** (p.37; **Compare with p.23**) Assume

- smooth coefficients,
- $f \in L_2$ .
- $\Gamma$  smooth, or  $\Gamma$  a convex polygon.

Then

$$\|u\|_2 \leq C\|f\|.$$

where  $C$  is independent of  $f$ .

This is a **regularity** result; it shows that  $u$  and its 1st and second derivatives can be bounded in terms of the data  $f$ , a rather remarkable fact.

**Note:** The result does not hold for regions in which  $\Gamma$  has an interior corner; for example, for an L-shaped domain.